

## **BASIC+** NET CFS Installer Netting

## **Basic+ Net Product Specs:**

Netting Material Type	BASIC + Installer Netting Multi-Filament Polypropylene (MFPP)			
Netting Degradation	Photodegradable			
Netting Diameters	8", 12", 18", 24", 32"			
Netting Opening Size	3/8″			
Netting Color	Black			
Fabric Tensile Strength (ASTM D4595) <sup>1</sup>	229 lbs			
Functional Longevity <sup>2</sup>	up to 4 years			



**Netting Sample** 

<sup>1</sup>Tensile Strength is based on 12" diameter using ATSM D4595. See Filtrexx TechLink #3342 for full tensile strength testing. <sup>2</sup>Functional longevity ranges are estimates only. Site specific environmental conditions may result in significantly shorter or longer time periods.

## **Item List:**

Item Number	Part Reference	Diameter	Unit Type	Length/Unit	Units per pallet	Feet per pallet
Installer - 8" Basic + Ruck	430-000251	8-in	Ruck	200-ft	112	22,400-ft
Installer - 12" Basic + Ruck	430-000255	12-in	Ruck	200-ft	120	24,000-ft
Installer - 18" Basic + Ruck	430-000260	18-in	Ruck	200-ft	90	18,000-ft
Installer - 24" Basic + Ruck	430-000262	24-in	Ruck	200-ft	70	14,000-ft
Installer - 32" Basic + Ruck	430-000263	32-in	Ruck	200-ft	60	12,000-ft



888-578-0777 mkbcompany.com

©2024 MKB Company. All Rights Reserved.



All statements, product characteristics, and performance data contained herein are believed to be reliable based on observation and testing, but no representations, guarantees, or warranties of any kind are made as to accuracy, suitability for particular applications, or the results to be obtained. Nothing contained herein is to be considered to be permission or a recommendation to use any proprietary process or technology without permission of the owner. No warranty of any kind, expressed or implied, is made or intended. Filtrexx<sup>®</sup>, Powered by Filtrexx<sup>®</sup>, the branch & leaf logo<sup>®</sup>, and the color GREEN<sup>®</sup> are Registered Trademarks of MKB Company. US Patents 7,226,240; 7,452,165; 8,439,607 and Patents Pending 62/964,021; 18/114,601 may apply.