

BASIC+ NET

CFS Installer Netting

Basic+ Net Product Specs:

| Netting Material Type | BASIC + Installer Netting Multi-Filament Polypropylene (MFPP) | | | |
|--|--|--|--|--|
| Netting Degradation | Photodegradable | | | |
| Netting Diameters | 8", 12", 18", 24", 32" | | | |
| Netting Opening Size | 3/8" | | | |
| Netting Color | Black | | | |
| Fabric Tensile Strength (ASTM D4595) ¹ | 229 lbs | | | |
| Functional Longevity ² | up to 4 years | | | |



Netting Sample

Item List:

| Part Number | Part Reference | Diameter | Unit Type | Length/Unit | Units per pallet | Feet per pallet |
|------------------------------|----------------|----------|-----------|-------------|------------------|-----------------|
| Installer - 8" Basic + Ruck | 430-000251 | 8-in | Ruck | 200-ft | 112 | 22,400-ft |
| Installer - 12" Basic + Ruck | 430-000255 | 12-in | Ruck | 200-ft | 120 | 24,000-ft |
| Installer - 18" Basic + Ruck | 430-000260 | 18-in | Ruck | 200-ft | 90 | 18,000-ft |
| Installer - 24" Basic + Ruck | 430-000262 | 24-in | Ruck | 200-ft | 70 | 14,000-ft |
| Installer - 32" Basic + Ruck | 430-000263 | 32-in | Ruck | 200-ft | 60 | 12,000-ft |

¹Functional longevity ranges are estimates only. Site specific environmental conditions may result in significantly shorter or longer time periods. ²Tensile Strength is based on 12" diameter using ATSM D4595. See Filtrexx TechLink #3342 for full tensile strength testing.