


# ENVIROSOXX®


## Pollutant Filter Sock

### EnviroSoxx Product Specs:

Netting Material Type	EXTREME Pallet Netting Multi-Filament Polypropylene (MFPP)
Netting Degradation	Photodegradable
Netting Diameters	8", 12"
Netting Opening Size	1/16"
Netting Color	Green/White Stripe (Industrial Blend) Green/Black Stripe (Advanced Blend)
Fabric Tensile Strength (ASTM D4595) <sup>1</sup>	929 lbs
Fill Type	Certified & Locally Sourced Composted FilterMedia™ + Natural Additives
Functional Longevity <sup>2</sup>	Quarterly replacement recommended
Staking Recommendation	Every 10-ft (stakes not included)



Netting Sample



Netting Sample



Fill Sample

<sup>1</sup>Tensile Strength is based on 12" diameter using ATSM D4595. See Filtrex TechLink #3342 for full tensile strength testing.

<sup>2</sup>Functional longevity ranges are estimates only. Site specific environmental conditions may result in significantly shorter or longer time periods.

### Item List:

Item Number (Industrial)	Item Number (Advanced)	Diameter	Total Linear Feet per pallet	Unit Length	Units per pallet	Pallet Weight
T08-80S8W	T08-80S8A	8-in	80-ft	10-ft	8	~ 1200 lbs
T08-160S16W	T08-160S16A	8-in	160-ft	10-ft	16	~ 1950 lbs
T08-160S2W	T08-160S2A	8-in	160-ft	80-ft	2	~ 1950 lbs
T12-50S5W	T12-50S5A	12-in	50-ft	10-ft	5	~ 1200 lbs
T12-100S10W	T12-100S10A	12-in	100-ft	10-ft	10	~ 1950 lbs
T12-100W	T12-100A	12-in	100-ft	100-ft	1	~ 1950 lbs

Note: Optional handles available as add-on

### Shipping Specs:

Pallets per TL	26
Shipping Dimensions	40L x 48W x 66H
Packaging	40 x 48 Pallet with Plastic Stretch-Wrap
Storage Life	Under Roof, with Ventilation - 6 months / Outdoors, Dry - 3 months